



Standards



Calibration standard	ISO12714
	GB/T 19801

Certification



Product description

The WI800 broadband built-in preamplifier integrated acoustic emission sensor has a frequency range of 50kHz-800kHz and a resonant frequency of 600kHz. Its broadband characteristics cover the frequency range of most acoustic emission applications. The collected signals are rich, comprehensive, and suitable for spectrum research, etc.

Product Feature

- SMA interface.
- The contact surface is made of ceramic material to isolate the outer shell from the measured object electromagnetically.
- The shell adopts SUS-304 and has an overall shielding design, effectively reducing interference.
- Each product has a unique serial number that can track the production testing process.
- Before leaving the factory, each sensor undergoes sensitivity testing in accordance with GB/T 19801-2005, and the response curve of the delivered products is actually measured.

Technical Specs

Resonant Freq. Ref V/(m/s)	600kHz	Sensitivity Peak Ref V/(m/s)	> 65dB
Frequency Range	50kHz-800kHz	Integral preamplifier	40dB28V
Working Temp.	-20 to 50°C	Size (DxH)	Φ22×25.5
Weight	32.29 g	Case Material	SUS-304
Face Material	Ceramic	Protecting Grade	IP62
Connector	SMA	Connector Location	Side

Accessories

Signal cable	RG178/RG316	Hold-down	Saddle type
---------------------	-------------	------------------	-------------